

Buren

Buren Watch Company SA
CH-3294 Büren a/A

Calibres de base	Grandeur	Calibres dérivés			∅ trou	Bloc dessus	Bloc dessous	Creusure plat. cad.	Clavette	Vis	Chaton empierré	Pierre de dessus	c. pivot dessous	Ressort de c. pivot dessus	Ressort de c. pivot dessous	
° 60	5½				08	100.11.245	112.20	10	—	180.19	150.21	111.08	121.11	122.11	173.03	172.03
° 65	5½				08	261.12.235	264.20	—	—	—	—	211.08	221.11	222.11	270.03	270.03
° 280	10½ 11½*	281*			09	261.21.293	264.20	10	7	280.17	—	211.09	222.11	222.11	270.03	270.03
° 300	8¾	301			08	100.21.260	100.20	10	16	180.15	150.11	111.08	122.11	122.11	170.03	170.03
° 350	6¾×8	351	352	353	08	100.11.245	111.20	10	—	180.19	150.11	111.08	121.11	122.11	173.03	171.03
° 355	8¾	356 359	357	358	08	100.11.260	100.20	—	—	180.19	150.11	111.08	121.11	122.11	170.03	170.03
° 360	5				08	201.11.245	211.20	10	—	280.21	150.21	211.08	221.11	222.11	270.03	270.03
° 370	10½	371			10	100.11.290	100.20	10	—	180.19	150.11	111.10	121.11	122.11	170.03	170.03
° 379	13				10	100.11.360	100.20	10	—	180.19	150.11	111.10	121.11	122.11	170.03	170.03
° 380	11½	381	382	383	09	100.11.305	100.20	10	—	180.19	150.11	111.09	121.11	122.11	170.03	170.03
° 410	10½	411			10	100.11.290	100.20	—	—	180.19	150.11	111.10	121.11	122.11	170.03	170.03
° 463	13				10	100.11.360	100.20	—	—	180.19	150.11	111.10	121.11	122.11	170.03	170.03
° 480	10½ 11½*	481*			10	100.11.290	100.20	10	—	180.19	150.11	111.10	121.11	122.11	170.03	170.03
° 525	12½				08	100.11.290	100.20	10	—	180.19	150.11	111.08	121.11	122.11	170.03	170.03
° 535	9¾	536 539	537 540	538	08	100.11.260	100.20	—	—	180.19	150.11	111.08	121.11	122.11	170.03	170.03
° 541	11½	542 545 549	543 546 547	544	08	100.11.260	100.20	—	—	180.19	150.11	111.08	121.11	122.11	170.03	170.03
° 1000	12½	1001 1005 1008	1002 1006 1007	1003	09	100.11.290	110.20	—	—	180.19	150.11	111.09	121.11	122.11	170.03	170.03
° 1280	12½	1281 1321	1282 1322	1320	08	261.12.235	264.20	10	—	—	—	211.08	221.11	222.11	270.03	270.03
° 1380	10½ 11½*	1381*			09	100.21.290	110.20	—	—	180.15	150.11	111.09	122.11	122.11	170.03	170.03
° 1420	10½ 11½*	1421*	1422*		09	100.11.290	110.20	—	—	180.19	150.11	111.09	121.11	122.11	170.03	170.03
01	19	02	03		12	513.11.420	513.20	—	—	580.25	—	511.12	521.11	522.11	570.03	570.03
11	13¾	12			09	163.22.312	185.20	—	—	—	—	111.09	122.11	122.11	170.03	175.03
86	5½	89			08	261.12.235	264.20	—	—	—	—	211.08	221.11	222.11	270.03	270.03
90	12½	91 95	92 96	93	08	261.12.235	264.20	10	—	—	—	211.08	221.11	222.11	270.03	270.03

