

# FEF

Fabrique d'Ebauches de Fleurier SA  
CH-2114 Fleurier

Calibres de base	Grandeur	Calibres dérivés	∅ trou	Bloc dessus	Bloc dessous	Creusure plat. cad.	Clavette	Vis	Chaton empierré	Pierre de dessus	c. pivot dessous	Ressort de c. pivot dessus	Ressort de c. pivot dessous
° 40 H	19 <sup>28</sup> / <sub>12</sub>		12	500.13.425	500.20	—	—	560.41	511.12	521.11	522.11	570.03	570.03
° 130	7¼ × 11		10	100.11.275	100.21	10	—	180.19	150.11	111.10	121.11	122.11	170.03
° 166	4 × 6		08	201.11.220	213.20	10	—	280.21	—	211.08	221.11	222.11	270.03
° 170	8 × 9	86 170 A	10	100.11.275	100.20	10	—	180.19	150.11	111.10	121.11	122.11	170.03
° 190	10½ 11½*	210*	10	100.11.345	100.20	10	—	180.19	150.11	111.10	121.11	122.11	170.03
° 250	8¾		09	100.11.275	100.20	10	—	180.19	150.11	111.09	121.11	122.11	170.03
° 270	5¼ × 8½		09	100.11.275	111.20	10	5	180.19	150.11	111.09	121.11	122.11	170.03
° 290	10½ 11½*	310*	10	100.11.345	100.20	10	—	180.19	150.11	111.10	121.11	122.11	170.03
° 350	10½ 11½*	380* 380-2	10	100.11.345	100.20	—	—	180.19	150.11	111.10	121.11	122.11	170.03
° 371	6¾ × 8	370	09	100.11.275	101.20	10	5	180.19	150.11	111.09	121.11	122.11	170.03
° 372	6¾ × 8	371 N 373	09	100.12.275	705.20	—	—	—	111.09 711.09	121.11	722.11	170.03	770.03
° 400	8¾	401	09	100.11.275	100.20	10	—	180.19	150.11	111.09	121.11	122.11	170.03
° 430	5 × 7		08	201.11.253	213.20	—	—	280.21	—	211.08	221.11	222.11	270.03
° 6600	5½ × 6¾	6620	08	201.11.253	213.20	—	—	280.21	—	211.08	221.11	222.11	270.03
6630	5½ × 6¾	6631 6700 6701 6710 6711 6720 6721	08	914.12.232	945.20	—	—	—	911.08 991.08	921.11	222.11	975.03	876.03
6640	4 × 6		08	205.21.210	213.20	10	—	280.17	—	211.08	222.11	270.03	270.03
6650	5 × 7		08	201.11.253	213.20	—	—	280.21	—	211.08	221.11	222.11	270.03
6660	6¾ × 8	6662	09	104.22.262	716.20	—	—	—	111.09 711.09	122.11	722.11	170.03	175.03
6670	8¾	6676 6677	09	944.22.262	946.20	—	—	—	911.09	922.11	922.11	974.03	975.03
6680	8¾	6686	09	944.22.262	946.20	10	—	—	911.09	922.11	922.11	974.03	975.03

FEF

par Fabrique d'horlogerie de Fontainemelon

CH-2052 Fontainemelon

° 6632	5½ × 6¾	6630 6631 6633 6700 6701 6710 6711 6720 6721	08	914.12.232	945.20	—	—	—	911.08 991.08	921.11	222.11	975.03	876.03
° 6640	4 × 6		08	205.21.210	213.20	10	—	280.17	—	211.08	222.11	270.03	270.03
° 6650	5 × 7		08	201.11.253	213.20	—	—	280.21	—	211.08	221.11	222.11	270.03
° 6660	6¾ × 8	6662 6663	09	104.22.262	716.20	—	—	—	111.09 711.09	122.11	722.11	170.03	775.03
° 6665	6¾ × 8	6664 6665-1 6764 6765	09	101.12.257	906.20	—	—	—	111.09 911.09	121.11	922.11	170.03	975.03
° 6670	8¾	6676 6677	09	944.22.262	946.20	—	—	—	911.09	922.11	922.11	974.03	975.03
° 6681	8¾	6680 6687	09	944.22.262	946.20	10	—	—	911.09	922.11	922.11	974.03	975.03

\* 277.00

5 1/2

08 104.22.262 946.20



111.08 122.11 922.11 170.03 975.03  
911.08