

Calibres de base	Grandeur	Calibres dérivés			∅ trou	Bloc dessus	Bloc dessous	Creusure plat. cad.	Clavette	Vis	Chaton empierré	Pierre dessus	c. pivot dessous	Ressort de dessus	c. pivot dessous
° 266	11½	286	291		10	103.21.312	100.20	— —	180.15	160.11	111.10	122.11	122.11	170.03	170.03
° 268	10½	269			10	201.21.310	219.20	10 3	280.17	150.21	211.10	222.11	222.11	270.03	270.03
° 273	7%	283	284	285	09	100.11.255	110.20	— —	180.19	160.11	111.09	121.11	122.11	170.03	170.03
° 275	6				08	201.11.210	211.20	10 —	280.21	150.21	211.08	221.11	222.11	270.03	270.03
° 280	6%				08	201.11.242	213.20	10 10	280.21	—	211.08	221.11	222.11	270.03	270.03
° 287	8%				09	100.11.275	100.20	10 —	180.19	160.11	111.09	121.11	122.11	170.03	170.03
° 294	7%				09	701.12.252	716.20	— —	—	—	711.09	721.11	722.11	775.03	775.03
° 295	11½	297	298		10	103.21.312	100.20	— —	180.15	160.11	111.10	122.11	122.11	170.03	170.03
° 301	7%	304	305	306	09	104.21.232	113.20	— —	180.15	—	111.09	122.11	122.11	173.03	173.03
° 526	19	552	554		12	500.13.420	500.20	— —	—	560.41	511.12	521.11	522.11	570.03	570.03
° 532	18				12	500.13.420	500.20	— —	—	560.41	511.12	521.11	522.11	570.03	570.03
° 616	16	618			12	500.13.420	500.20	— —	—	560.41	511.12	521.11	522.11	570.03	570.03
° 635	5%				09	100.11.260	112.20	10 —	180.19	150.21	111.09	121.11	122.11	170.03	172.03
° 650	5½	652			09	100.11.260	112.20	10 17	180.19	150.21	111.09	121.11	122.11	170.03	172.03
° 654	5½				08	100.11.260	112.20	10 17	180.19	150.21	111.08	121.11	122.11	170.03	172.03
° 657	8%	658			09	100.21.275	100.20	10 —	180.15	150.11	111.09	122.11	122.11	170.03	170.03
° 677	12	678			10	100.11.300	100.20	10 —	180.19	150.11	111.10	121.11	122.11	170.03	170.03
° 686	6¾×8	687			09	100.11.275	112.20	10 3	180.19	150.21	111.09	121.11	122.11	170.03	172.03
° 693	10½	694			10	100.11.300	100.20	10 —	180.19	150.11	111.10	121.11	122.11	170.03	170.03
° 696	10½ 11½*	697* 700* 706* 710*	698* 703* 707*	699* 704* 709*	10	100.11.300	100.20	— —	180.19	150.11	111.10	121.11	122.11	170.03	170.03
° 712	7%				09	201.12.210	213.20	10 —	—	—	211.09	221.11	222.11	270.03	270.03
° 718	16	723			11	500.11.400	500.20	— 15	180.15	—	111.11	122.11	122.11	170.03	173.03
° 720	13				09	100.22.285	100.20	— —	—	150.11	111.09	122.11	122.11	170.03	170.03
° 726	18½	731			12	500.13.480	500.20	— —	—	560.41	511.12	521.11	522.11	570.03	570.03
276	6%				08	100.21.255	110.20	— —	180.15	160.11	111.08	122.11	122.11	170.03	170.03
292	10½	316			10	100.11.310	103.20	— —	180.19	—	111.10	121.11	122.11	170.03	173.03
307	11½	310			09	944.22.312	946.20	10 —	—	—	911.09	922.11	922.11	974.03	975.03
311	6				08	103.21.252	113.20	— —	180.15	—	111.08	122.11	122.11	170.03	173.03
313	8%				09	100.11.275	100.20	10 —	180.19	150.11	111.09	121.11	122.11	170.03	170.03
325	11½	326	327		10	163.22.312	163.20	— —	—	—	111.10	122.11	122.11	170.03	173.03
350	12½				10	706.21.000	706.21	— —	—	—	711.10	722.11	722.11	775.03	775.03
654-1	5½				09	201.22.210	213.20	— 17	—	—	211.09	222.11	222.11	270.03	270.03
734	13				11	180.12.360	906.20	— —	—	—	111.11 911.11	121.11	922.11	170.03	975.03
736	18½	737	738		12	441.12.480	445.20	— —	—	—	411.12	421.12	422.12	470.03	476.03
739	13	734 N	740	741	11	180.12.360	906.20	— —	—	—	111.11 911.11	121.11	922.11	170.03	975.03
745	16½	746			12	444.12.412	475.20	10 —	—	—	411.12	421.12	422.12	470.03	476.03

