

**SEIKO**

**QUARTZ**

**Cal. 2620A**

**PARTS LIST**

# Cal. 2620A



131 262	231 260	241 262	261 260	☆270 262	☆271 262	281 261
282 262	☆354 261	☆354 263	383 260	384 261	387 261	389 260
391 260	436 261	491 260	493 260	495 260	701 260	706 260
☆4001 262	4002 261	4146 260	4216 260	4219 261	4239 260	4242 260
4270 260	4455 260	011 409	☆SEIKO SB-DL			

012 151	012 159	012 459	012 768	017 125	017 126	017 127	017 129	017 131
								$\frac{2}{1}$
017 132	017 159	017 936						$\frac{2}{1}$

# Cal. 2620A

## Characteristics:

Casing diameter:  $\phi$  17.60 mm  
 Maximum height: 3.00 mm without battery  
 Jewels: 2 j  
 Frequency of quartz crystal oscillator: 32,768 Hz (Hz=Hertz . . . . . Cycle per second)  
 Driving system: Step motor system (2 poles)  
 Regulation system: Trimmer condenser

PART NO.	PART NAME	PART NO.	PART NAME
<b>131 262</b>	Third wheel bridge	<b>4239 260</b>	Rotor stator
<b>231 260</b>	Third wheel & pinion	<b>4242 260</b>	Plus terminal of battery connection
<b>241 262</b>	Fourth wheel & pinion	<b>4270 260</b>	Battery connection
<b>261 260</b>	Minute wheel	<b>4455 260</b>	Reset lever
☆ <b>270 262</b>	Center minute wheel with cannon pinion (1.74 mm)	<b>011 409</b>	Upper hole jewel for step rotor
☆270 265	Center minute wheel with cannon pinion (2.26 mm)	<b>011 409</b>	Lower hole jewel for step rotor
☆270 266	Center minute wheel with cannon pinion (1.84 mm)	<b>012 151</b>	Third wheel bridge screw
☆270 267	Center minute wheel with cannon pinion (2.85 mm)	<b>012 151</b>	Circuit block screw A
☆270 274	Center minute wheel with cannon pinion (1.74 mm)	<b>012 151</b>	Coil block screw (Screw for plus terminal of battery connection)
☆270 275	Center minute wheel with cannon pinion (2.26 mm)	<b>012 159</b>	Circuit block screw B
☆270 276	Center minute wheel with cannon pinion (1.84 mm)	<b>012 459</b>	Case screw
☆270 277	Center minute wheel with cannon pinion (2.85 mm)	<b>012 768</b>	Setting lever axle spring screw
☆ <b>271 262</b>	Hour wheel (0.85 mm)	<b>012 768</b>	Minute wheel bridge screw
☆271 266	Hour wheel (0.95 mm)	<b>017 125</b>	Tube for circuit block A
☆271 267	Hour wheel (1.37 mm)	<b>017 126</b>	Tube for circuit block B
☆271 268	Hour wheel (1.91 mm)	<b>017 127</b>	Tube for circuit block C
<b>281 261</b>	Setting wheel	<b>017 129</b>	Tube for third wheel bridge screw A
<b>282 262</b>	Clutch wheel	<b>017 131</b>	Tube for coil block screw
☆ <b>354 261</b>	Winding stem (13.13 mm)	<b>017 132</b>	Second setting lever pin
☆ <b>354 263</b>	Winding stem (18.58 mm)	<b>017 159</b>	Tube for third wheel bridge screw B
<b>383 260</b>	Setting lever	<b>017 936</b>	Eccentric dial pin
<b>384 261</b>	Yoke (Clutch lever)	☆SEIKO SB-DL	Silver peroxide battery
<b>387 261</b>	Minute wheel bridge		
<b>389 260</b>	Setting lever axle spring		
<b>391 260</b>	Second setting lever		
<b>436 261</b>	Lower end-piece for third wheel		
<b>491 260</b>	Dial washer		
<b>493 260</b>	Hour wheel ring (Gold, 0.03mm thickness)		
493 261	Hour wheel ring (Silver, 0.05mm thickness)		
493 262	Hour wheel ring (Gold, 0.10 mm thickness)		
<b>495 260</b>	Spacer for third wheel bridge		
<b>701 260</b>	Fifth wheel & pinion		
<b>706 260</b>	Sixth wheel & pinion		
☆ <b>4001 262</b>	Circuit block		
☆4001 270			
<b>4002 261</b>	Coil block		
<b>4146 260</b>	Step rotor		
<b>4216 260</b>	Insulator for battery		
<b>4219 261</b>	Insulator for battery connection		









☆⇨ Please see remarks on the reverse page.  
 Part numbers in light letters are not shown in photos.

# Cal. 2620A

## Remarks:

Center minute wheel with cannon pinion, Hour wheel

Combination:

Type	a		b		c		d	
Center minute wheel with cannon pinion		Gold plated		Gold plated		Gold plated		Gold plated
	☆270 262	☆270 274	☆270 265	☆270 275	☆270 266	☆270 276	☆270 267	☆270 277
Hour wheel								
	Silver		Silver		Gold		Silver	
	☆271 262		☆271 267		☆271 266		☆271 268	

**Winding stem**.....Refer to the photograph on the front page.

☆354 261.....Short winding stem (Thread is provided completely on the crown portion.)

☆354 263.....Long winding stem (Thread is provided only on the end of the crown portion.)

If the combination of the winding stem and case is unknown, check the case number and refer to "SEIKO Quartz Casing Parts List" to choose an appropriate winding stem.

### Circuit block

☆4001 262.....4001 270 can be used as 4001 262.  
(☆4001 270)

### Coil block

☆4002 261.....The parts that have the same parts No. as 4002 261 are interchangeable, even if the color of that parts is different.

### Battery

☆SEIKO SB-DL.....The applied battery for this calibre might be added the substitutive in the future. In that case, please refer to separate "BATTERIES FOR SEIKO QUARTZ WATCHES".