


Catalog No.



Cal. 6105B

Characteristics

Casing diameter: 27.00 ϕ mm
 Maximum height: 5.15 mm
 Vibrations per hour: 21,600
 Automatic winding with sweep second
 Calender (date)
 Instant date setting (rotating crown)
 Second-setting device
 "Diashock" Shock Resistant Device

112619

122619

171619

282619

345612

383615

384615

385615

387615

388615

193552

500620

823619

802616

803615

808619

814615

990616

354617

022269

022458

022493

022761 $\frac{3}{4}$

Calibre No. 6105B		Jewels 17j	Style Name	
\Rightarrow Basic Calibre 6106A 25J Catalog No. 61-06-1				
PART NO.	LIST OF MATERIALS	PART NO.	LIST OF MATERIALS	
112619	Barrel & train-wheel bridge	☆801610	Date dial	
122619	Center wheel bridge	802616	Date driving wheel	
161805	Pallet cock	803615	Setting wheel lever complete	
171619	Balance cock	808619	Date dial guard	
193552	Framework for automatic device with ball-bearing	810619	Date jumper	
205613	Complete barrel with arbor	814615	Setting wheel lever plate	
213612	Barrel arbor	817610	Intermediate date wheel	
224611	Center wheel & pinion with cannon pinion	☆884611	Holding ring for dial	
225611	Cannon pinion	990616	Date driving wheel holder	
231610	Third wheel & pinion	022150	Stud screw	
241611	Sweep second wheel & pinion	022252	Holder screw for transmission wheel & pawl lever	
251611	Escape wheel & pinion	022269	Minute wheel bridge screw	
261611	Minute wheel	022351	Center wheel bridge screw	
271611	Hour wheel	022458	Screw for oscillating weight	
282619	Clutch wheel	022467	Ratchet wheel screw	
285611	Ratchet wheel	022468	Pallet cock screw	
301611	Jewelled pallet fork & staff	022470	Framework screw for automatic device with ball-bearing	
310611	Balance complete with stud	022471	Click screw	
315611	Balance staff	022493	Bridge screw	
331610	Roller with jewel	022662	Setting lever spring screw	
341611	Regulator	022760	Date dial guard screw	
345612	Stud holder	022760	Setting wheel lever plate screw	
354617	Winding stem	022761	Dial screw	
381611	Click	011145	Upper hole jewel for center wheel	
383615	Setting lever with axle	011146	Lower hole jewel for center wheel	
384615	Yoke (Clutch lever)	011306	Lower hole jewel for 3rd wheel	
385615	Yoke spring (Clutch lever spring)	011406	Upper hole jewel for escape wheel	
387615	Minute wheel bridge	011406	Lower hole jewel for escape wheel	
388615	Setting lever spring	011503	Upper hole jewel for pallet	
391610	Second-setting lever	011503	Lower hole jewel for pallet	
☆397610	Lever for unlocking stem	011147	Upper hole jewel for transmission wheel	
401615	Mainspring with slipping attachment	011147	Lower hole jewel for transmission wheel	
014363	Diashock upper frame	023150	Tube for pallet cock screw (Cylinder type)	
014364	Diashock lower frame	023151	Tube for bridge screw	
014365	Diashock hole jewel with frame	023170	Tube for pallet cock screw (Recessed type)	
011210	Diashock cap jewel	023171	Tube for framework screw of automatic device	
014317	Diashock spring			
500620	Oscillating weight			
505611	Transmission wheel			
823619	Eccentric post			
831611	Pawl lever with jewel			
839610	Holder for transmission wheel & pawl lever			

Remarks :

Lever for unlocking stem
 ☆397610.....Used only for the one-piece waterproof case.

Date dial
 ☆801610 (Black figures on white background).....Used when the crown is located at 4 o'clock and the date frame at 3 o'clock.

If the date dial is required in any other type, specify ① Cal. No. ② the crown position ③ the date frame position and ④ the dial No.

Holding ring for dial ----- Measure the total thickness and the outside diameter -----
 ☆884611.....1.82mm total thickness and 29.1 ϕ mm outside diameter

If the holding ring for dial is required in any other type, specify ① Cal. No. and ② the dial No.

As for all other parts not shown here, please refer to the basic calibre (Cal. No. 6106A 25J Catalog No. 61-06-1 Green page).

☆ \Rightarrow Please see remarks.

Items in light letters are not shown in photos; those parts are interchangeable with the basic calibre

(Cal. No. 6106A 25J Catalog No. 61-06-1 Green page).