

ADEC QUARTZ Model No. HT7 XXX Cal. No. DD70

INSTRUCTION MANUAL

■ SPECIFICATIONS

- 1) Type Digital quartz watch
- 2) Accuracy 45 seconds per month on average (when worn at normal temperatures of +5°C to +35°C)
- 3) Operating temperature range 0°C to +50°C

4) Basic functions

- Time: hours, minutes, seconds, 12/24-hour clock
- Calendar: month, date, day, year (1997-2099)
- Alarm 1: hours, minutes, 12/24-hour clock
- Alarm 2: hours, minutes, 12/24-hour clock
- Stopwatch: 24-hour measurement, 1/100 second units (up to 60 minutes), split time measurement

5) Additional functions

- Alarm monitor
 - EL internal illumination function
- Battery No. 280-209, battery code: CR1616


6) Batteries

7) Battery life


- Approximately 3 years (in the case of the alarm sounding for 30 seconds per day and using EL illumination for 3 seconds per day)

*Specifications are subject to change without notice.

■ Explanation of Displays and Buttons




■ Selection of Display




<Normal time display mode>

1 HOW TO SET TIME AND DATE




2 ALARM SETTING (1 & 2)



3 STOPWATCH

Minutes (hours after 60 minutes have elapsed)


1/100 seconds (seconds after 60 minutes have elapsed)



5 USING THE EL FUNCTION

Pressing button **C** or **D** causes EL internal illumination to be turned on.

6 GRAPHIC DISPLAY



* The graphic display is shown once every 60 seconds. When a button has not been pressed for 12 hours or more, however, the graphic display is shown once every 10 seconds.
 * In addition, the graphic display is also shown whenever the mode is changed.