

Becker

Hermann Becker KG
D-7531 Dietlingen bei Pforzheim

Calibres de base	Grandeur	Calibres dérivés	∅ trou	Bloc dessus	Bloc dessous	Creusure plat. cad.	Clavette	Vis	Chaton empierré	Pierre de dessus	c. pivot dessous	Ressort de dessus	c. pivot dessous	
° 80	6¼ × 8		09	100.11.275	102.20	10	3	180.19	150.21	111.09	121.11	122.11	170.03	172.03
° 80	6¼ × 8	81 82	09	100.12.275	103.20	10	3	—	—	111.09	121.11	122.11	170.03	173.03
° 110	10½ 11½*	111* 112* 113* 114* 312* 313* 314*	09	100.11.300	100.20	—	—	180.19	150.11	111.09	121.11	122.11	170.03	170.03
° 115	11½	120 1151	09	100.11.300	100.20	10	—	180.19	150.11	111.09	121.11	122.11	170.03	170.03
90	6¼ × 8		09	100.12.275	906.20	—	—	—	—	111.09 911.09	121.11	922.11	170.03	975.03
0111	11½	312 313 314	09	100.12.300	103.20	—	—	—	—	111.09	121.11	122.11	170.03	175.03
411	11½	412 413 414	09	100.12.300	926.20	—	—	—	—	111.09 911.09	121.11	922.11	170.03	975.03

Calibres de base	Grandeur	Calibres dérivés	∅ trou	Bloc dessus	Bloc dessous	Creusure plat. cad.	Clavette	Vis	Chaton empierré	Pierre de dessus	c. pivot dessous	Ressort de dessus	c. pivot dessous	
BECKER	Hermann Becker KG	D-7531 Keltern 1												
° 80	6¼ × 8	81 82	09	100.12.275	103.20	10	3	—	—	111.09	121.11	122.11	170.03	173.03
° 311	11½	312 313 314	09	100.12.300	103.20	—	—	—	—	111.09	121.11	122.11	170.03	173.03
90	6¼ × 8		09	100.12.275	906.20	—	—	—	—	111.09 911.09	121.11	922.11	170.03	975.03
411	11½	412 413 414	09	100.12.300	926.20	—	—	—	—	111.09 911.09	121.11	922.11	170.03	975.03
900	6¼ × 8		09	100.12.275	906.20	—	—	—	—	111.09 911.09	121.11	922.11	170.03	975.03
BIFORA	Bifora Uhren G.m.b.H.	D-707 Schwäbisch-Gmünd												
° 130	13	130 Dat.	10	180.22.300	185.20	—	(1)	—	—	111.10	122.11	122.11	170.03	175.03
52	5½	52/2	09	183.22.262	727.20	—	—	—	—	111.09 711.09	122.11	722.11	170.03	775.03
69	6¼ × 8	69 Dat. 691 691Dat.	09	183.22.262	727.20	—	—	—	—	111.09 711.09	122.11	722.11	170.03	775.03
115	11½	115 Dat. 115/1 115/1Dat.	10	180.22.300	185.20	—	—	—	—	111.10	122.11	122.11	170.03	175.03
° 49	5		09	100.11.265	112.20	—	—	180.19	150.21	111.09	121.11	122.11	170.03	172.03
° 51	5½		09	100.11.265	112.20	10	20	180.19	150.21	111.09	121.11	122.11	170.03	172.03
° 70	7¼	70 Aut.	09	100.11.265	112.20	10	20	180.19	150.21	111.09	121.11	122.11	170.03	172.03
52	5½	52/2	09	100.22.262	725.20	—	—	—	—	111.09 711.09	122.11	722.11	170.03	770.03
69	6¼ × 8	69 Dat. 691Dat.	09	183.22.262	727.20	—	—	—	—	111.09 711.09	122.11	722.11	170.03	175.03
115	11½	115 Dat. 115/1	10	180.22.300	185.20	—	—	—	—	111.10	122.11	122.11	170.03	175.03
120	12½	120 SG	10	100.11.295	100.20	—	—	180.19	150.11	111.10	121.11	122.11	170.03	170.03
130	13	130 Dat.	10	180.22.300	185.20	—	(1)	—	—	111.10	122.11	122.11	170.03	175.03