

Calibres de base	Grandeur	Calibres dérivés	∅ trou	Bloc dessus	Bloc dessous	Creusure plat. cad.	Clavette	Vis	Chaton empierré	Pierre de dessus	c. pivot dessous	Ressort de c. pivot dessus	Ressort de c. pivot dessous
EBEL	Fabrique Ebel SA	CH-2300	La	Chaux-de-Fonds									
° 30	11½	20 32	08	164.22.312	173.20	— — —	—	—	111.08	122.11	122.11	170.03	173.03
° 31	3%		75	271.11.242	264.20	10 —	180.19	—	211.75	221.11	222.11	270.03	270.03
°047	4%	47	75	100.11.235	112.20	10 6	180.19	150.21	111.75	121.11	122.11	173.03	172.03
°050	5	50	75	100.11.255	112.20	10 —	180.19	150.21	111.75	121.11	122.11	170.03	172.03
° 52	5½		75	201.11.253	213.20	— —	280.21	—	211.75	221.11	222.11	270.03	270.03
°055	5½		75	100.11.255	113.20	10 —	180.19	—	111.75	121.11	122.11	170.03	173.03
° 67	6%		08	103.22.252	113.20	— —	—	—	111.08	122.11	122.11	170.03	173.03
° 71	7%		08	104.21.232	113.20	— —	180.15	—	111.08	122.11	122.11	173.03	173.03
° 72	7%		08	104.21.232	113.20	— —	180.15	—	111.08	122.11	122.11	173.03	173.03
° 97	10½		08	211.21.308	219.20	10 9	280.17	160.21	211.08	222.11	222.11	270.03	270.03
°97B	10½		08	100.21.310	119.20	10 19	180.15	—	111.08	122.11	122.11	170.03	173.03
°212	11½	312 512 612	09	103.21.312	100.20	— —	180.15	160.11	111.09	122.11	122.11	170.03	170.03
°213	11½	214 313 314	08	138.21.283	103.20	10 9	180.15	—	111.08	122.11	122.11	173.03	173.03
°214A	11½	313 314	08	103.21.262	103.20	10 9	180.15	—	111.08	122.11	122.11	170.03	173.03
°215	11½		08	103.21.262	103.20	10 9	180.15	—	111.08	122.11	122.11	170.03	173.03
°222	11½	322 422	09	163.22.312	163.20	— —	—	—	111.09	122.11	122.11	170.03	173.03
°222B	11½	322B 422B	09	163.22.312	163.20	— —	—	—	111.09	122.11	122.11	170.03	173.03
°336	11½	436 Triovis	08	164.22.232	173.20	— —	—	—	111.08	122.11	122.11	173.03	173.03
29	12½		09	164.22.262	173.20	— —	—	—	111.09	122.11	122.11	170.03	173.03
59	5%	059	07	201.11.210	211.20	10 —	280.21	150.21	211.07	221.11	222.11	270.03	270.03
61	6		07	103.22.252	113.20	— —	—	—	111.07	122.11	122.11	170.03	173.03
78	7%		08	103.22.278	113.20	10 20	—	—	111.08	122.11	122.11	170.03	173.03
107	10%		08	944.22.290	946.20	10 13	—	—	911.08	922.11	922.11	974.03	975.03
107	10%	Triovis	08	944.22.262	946.20	10 13	—	—	911.08	922.11	922.11	974.03	975.03
152	5%		75	914.12.232	945.20	— —	—	—	911.75 991.75	921.11	222.11	975.03	876.03
172	7%	170	07	104.22.232	113.20	— —	—	—	111.07	122.11	122.11	173.03	173.03

= 172.66

7¾

170.66

Ebel

Fabrique Ebel SA
CH-2300 La Chaux-de-Fonds

Calibres de base	Grandeur	Calibres dérivés			∅ trou	Bloc dessus	Bloc dessous	Creusure plat. cad.	Clavette	Vis	Chaton empierré	Pierre de c. pivot		Ressort de c. pivot	
												dessus	dessous	dessus	dessous
° 047	4%	47			75	100.11.235	112.20	10 6	180.18	150.21	111.75	121.11	122.11	173.03	172.03
° 050	5	50			75	100.11.255	112.20	10 —	180.19	150.21	111.75	121.11	122.11	170.03	172.03
° 52	5½				75	201.11.253	213.20	— —	280.21	—	211.75	221.11	222.11	270.03	270.03
° 055	5½				75	100.11.255	113.20	10 —	180.19	—	111.75	121.11	122.11	170.03	173.03
° 56	5½				75	100.11.255	113.20	— —	180.19	—	111.75	121.11	122.11	170.03	173.03
° 60	6				75	201.11.210	211.20	10 —	280.21	150.21	211.75	221.11	222.11	270.03	270.03
° 67	6%				08	100.21.255	110.20	— —	180.15	160.11	111.08	122.11	122.11	170.03	170.03
° 73	7%	74			08	100.11.255	110.20	— —	180.19	160.11	111.08	121.11	122.11	170.03	170.03
° 76	7%				08	100.11.255	113.20	— —	180.19	—	111.08	121.11	122.11	170.03	173.03
° 77	7%				08	100.11.240	111.20	10 —	180.19	150.11	111.08	121.11	122.11	170.03	171.03
° 86	8%				08	100.11.282	100.20	10 —	180.19	160.11	111.08	121.11	122.11	170.03	170.03
° 88	8%				09	100.11.255	100.20	10 —	180.19	150.11	111.09	121.11	122.11	170.03	170.03
° 97	10½				08	211.21.308	219.20	10 9	280.17	160.21	211.08	222.11	222.11	270.03	270.03
° 106	10½	116			08	100.21.305	100.20	10 15	180.15	150.11	111.08	122.11	122.11	170.03	170.03
° 111	11½ 10½*	110*	211	311	08	100.21.317	100.20	— —	180.15	160.11	111.08	122.11	122.11	170.03	170.03
° 111	11½				08	103.21.312	100.20	— —	180.15	160.11	111.08	122.11	122.11	170.03	170.03
° 113	11½	114			08	100.21.310	100.20	— —	180.15	160.11	111.08	122.11	122.11	170.03	170.03
° 116	11½				08	100.21.305	100.20	10 15	180.15	150.11	111.08	122.11	122.11	170.03	170.03
° 120	12				09	100.11.310	100.20	10 —	180.19	160.11	111.09	121.11	122.11	170.03	170.03
° 130	12				09	100.11.317	100.20	— —	180.19	150.11	111.09	121.11	122.11	170.03	170.03
° 212	11½	312	512	612	09	103.21.312	100.20	— —	180.15	160.11	111.09	122.11	122.11	170.03	170.03
° 222	11½	322	422		09	103.21.312	103.20	— —	180.15	—	111.09	122.11	122.11	170.03	173.03
° 222 B	11½	322 B	422 B		09	163.22.312	163.20	— —	—	—	111.09	122.11	122.11	170.03	173.03
30	11½	32			08	164.22.312	173.20	— —	—	—	111.08	122.11	122.11	170.03	173.03
31	3%				75	271.11.242	264.20	10 —	180.19	—	211.75	221.11	222.11	270.03	270.03
047	4%				75	100.11.235	112.20	10 6	180.19	150.21	111.75	121.11	122.11	173.03	172.03
59	5%	059			07	201.11.210	211.20	10 —	280.21	150.21	211.07	221.11	222.11	270.03	270.03
61	6				07	103.22.252	113.20	— —	—	—	111.07	122.11	122.11	170.03	173.03
67	6%				08	103.22.252	113.20	— —	—	—	111.08	122.11	122.11	170.03	173.03
71	7%				08	104.21.232	113.20	— —	180.15	—	111.08	122.11	122.11	173.03	173.03
72	7%				08	104.21.232	113.20	— —	180.15	—	111.08	122.11	122.11	173.03	173.03
78	7%				08	103.22.278	113.20	10 20	—	—	111.08	122.11	122.11	170.03	173.03
97 B	10½				08	100.21.310	119.20	10 19	180.15	—	111.08	122.11	122.11	170.03	173.03
152	5%				75	914.12.232	945.20	— —	—	—	911.75 991.75	921.11	222.11	975.03	876.03
172	7%				07	104.22.232	113.20	— —	—	—	111.07	122.11	122.11	173.03	173.03
213	11½	214	313	314	08	138.21.283	103.20	10 9	180.15	—	111.08	122.11	122.11	170.03	173.03
214	11½	313	314		08	103.21.262	103.20	10 9	180.15	—	111.08	122.11	122.11	170.03	173.03
215	11½				08	103.21.262	103.20	10 9	180.15	—	111.08	122.11	122.11	170.03	173.03

