

ETA

ETA SA

CH-2540 Grenchen

° 746	4¼ × 10		09	100.11.255	111.20	-	-	180.19	150.11	111.09	121.11	122.11	170.03	171.03
° 980	8¾	978	09	100.21.255	100.20	10	20	180.15	150.11	111.09	122.11	122.11	170.03	170.03
° 1080	10½ 11½	1081 1082 1083 1093 1152 1153	10	103.11.312	100.20	-	-	180.19	150.11	111.10	121.11	122.11	170.03	170.03
° 1120	12 13	1121 1162 1164 1292 1293	11	103.11.312	100.20	10	-	180.19	150.11	111.11	121.11	122.11	170.03	170.03
* 2000 ° 1280 ° 2325	10½ 11½	1281	10	103.11.312	100.20	10	-	180.19	160.11	111.10	121.11	122.11	170.03	170.03
° 2360	8¾	2335	09	100.11.282	100.20	10	-	180.19	160.11	111.09	121.11	122.11	170.03	170.03
° 2365	7¾	2363	09	100.11.255	110.20	-	-	180.19	160.11	111.09	121.11	122.11	170.03	170.03
° 2370	7¾ 8¾	2366 2367 2368 2369	09	100.11.255	110.20	-	-	180.19	160.11	111.09	121.11	122.11	170.03	170.03
° 2375	11½	2372 2373	10	103.11.312	100.20	-	-	180.19	160.11	111.10	121.11	122.11	170.03	170.03
° 2390	11½	2378	10	100.11.317	100.20	-	-	180.19	160.11	111.10	121.11	122.11	170.03	170.03
° 2412	10½ 11½	2391 2408 2409	10	103.21.312	100.20	-	-	180.15	160.11	111.10	122.11	122.11	170.03	170.03
° 2425	6¾		08	103.22.252	113.20	-	-	-	-	111.08	122.11	122.11	170.03	173.03
° 2442	6¾	2428	08	103.21.252	110.20	-	-	180.15	160.11	111.08	122.11	122.11	170.03	170.03
° 2450	6		08	103.22.252	113.20	-	-	-	-	111.08	122.11	122.11	170.03	173.03
° 2485	10½ 11½	2451 2452 2453 2454 2458 2459 2460 2472 2474	10	103.21.312	100.20	-	-	180.15	160.11	111.10	122.11	122.11	170.03	170.03
° 2490	5½ × 6¾	2487	08	100.11.255	113.20	-	-	180.19	-	111.08	121.11	122.11	170.03	173.03
	8¾	2491 2493	09	103.21.262	100.20	-	-	180.15	160.11	111.09	122.11	122.11	170.03	170.03

\* 2000  
808 82832 878.20  
190

277.001 See front inside Cover.

Calibres de base	Grandeur	Calibres dérivés			∅ trou	Bloc dessus	Bloc dessous	Creusure plat. cad.	Clavette	Vis	Chaton empierré	Pierre de dessus	c. pivot dessous	Ressort de c. pivot dessus	c. pivot dessous
° 746	4¼×10				09	100.11.255	111.20	— —	180.19	150.11	111.09	121.11	122.11	170.03	171.03
° 980	8%	978			09	100.21.255	100.20	10 20	180.15	150.11	111.09	122.11	122.11	170.03	170.03
° 1080	10½ 11½	1081 1093	1082 1152	1083 1153	10	103.11.312	100.20	— —	180.19	150.11	111.10	121.11	122.11	170.03	170.03
° 1120	12 13	1121 1292	1162 1293	1164	11	103.11.312	100.20	10 —	180.19	150.11	111.11	121.11	122.11	170.03	170.03
° 1256	11½	1257	1258	1259	10	100.11.317	100.20	— —	180.19	150.11	111.10	121.11	122.11	170.03	170.03
° 1260	10½ 11½	1261			10	100.11.317	100.20	— —	180.19	160.11	111.10	121.11	122.11	170.03	170.03
° 1280	10½ 11½	1281			10	103.11.312	100.20	10 —	180.19	160.11	111.10	121.11	122.11	170.03	170.03
° 1301	8%				09	100.11.282	100.20	10 —	180.19	160.11	111.09	121.11	122.11	170.03	170.03
° 1302	8%				09	100.11.282	100.20	10 4	180.19	160.11	111.09	121.11	122.11	170.03	170.03
° 1306	8%...10½	1307 1310	1308	1309	09	100.11.282	100.20	10 —	180.19	160.11	111.09	121.11	122.11	170.03	170.03
° 1311	8%				09	100.11.282	100.20	10 —	180.19	160.11	111.09	121.11	122.11	170.03	170.03
° 1312	8%				09	100.11.282	100.20	10 4	180.19	160.11	111.09	121.11	122.11	170.03	170.03
° 1316	8%...10½	1315 1320	1317	1318	09	100.11.282	100.20	10 —	180.19	160.11	111.09	121.11	122.11	170.03	170.03
° 2325	8%	2335			09	100.11.282	100.20	10 —	180.19	160.11	111.09	121.11	122.11	170.03	170.03
° 2340	5¼×8½				09	100.11.282	100.20	10 —	180.19	160.11	111.09	121.11	122.11	170.03	170.03
° 2345	5¼×8½				09	100.11.282	100.20	10 —	180.19	160.11	111.09	121.11	122.11	170.03	170.03
° 2360	7%	2363			09	100.11.255	110.20	— —	180.19	160.11	111.09	121.11	122.11	170.03	170.03
° 2365	7% 8%	2366 2369	2367	2368	09	100.11.255	110.20	— —	180.19	160.11	111.09	121.11	122.11	170.03	170.03
° 2370	11½	2372	2373		10	103.11.312	100.20	— —	180.19	160.11	111.10	121.11	122.11	170.03	170.03
° 2375	11½	2378			10	100.11.317	100.20	— —	180.19	160.11	111.10	121.11	122.11	170.03	170.03
° 2382	11½				10	100.11.317	100.20	— —	180.19	160.11	111.10	121.11	122.11	170.03	170.03
° 2390	10½ 11½	2391	2408	2409	10	103.21.312	100.20	— —	180.15	160.11	111.10	122.11	122.11	170.03	170.03
° 2410	8%	2412			08	100.21.255	110.20	— —	180.15	160.11	111.08	122.11	122.11	170.03	170.03
° 2425	6%	2428			08	103.21.252	110.20	— —	180.15	160.11	111.08	122.11	122.11	170.03	170.03
° 2440	6	2442			08	100.21.255	113.20	— —	180.15	—	111.08	122.11	122.11	170.03	173.03
° 2450	10½ 11½	2451 2454 2460	2452 2458 2472	2453 2459 2474	10	103.21.312	100.20	— —	180.15	160.11	111.10	122.11	122.11	170.03	170.03
° 2480	5¼×6%	2482			08	100.11.255	113.20	— —	180.19	—	111.08	121.11	122.11	170.03	173.03
° 2485	5¼×6%	2487			08	100.11.255	113.20	— —	180.19	—	111.08	121.11	122.11	170.03	173.03
° 2490	8%	2491	2493		09	103.21.262	100.20	— —	180.15	160.11	111.09	122.11	122.11	170.03	170.03
° 2492	8%				09	104.22.262	113.20	— —	—	—	111.09	122.11	122.11	170.03	173.03
° 2500	11½	2502	2508	2516	10	103.21.312	100.20	— —	180.15	160.11	111.10	122.11	122.11	170.03	170.03
° 2510	7%	2512			09	100.21.282	110.20	10 20	180.15	160.11	111.09	122.11	122.11	170.03	170.03
2512-1	7½%				09	103.21.278	113.20								
° 2520	11½ 13	2522 2533*	2523* 2538	2532 2539*	10	103.21.312	100.20	— —	180.15	160.11	111.10	122.11	122.11	170.03	170.03
° 2540	7%	2541			09	104.21.232	113.20	— —	180.15	—	111.09	122.11	122.11	173.03	173.03
° 2550	7%	2551			09	104.21.232	113.20	— —	180.15	—	111.09	122.11	122.11	173.03	173.03
° 2600	11½	2602	2608	2609	10	163.22.312	163.20	— —	—	—	111.10	122.11	122.11	170.03	173.03



Calibres de base	Grandeur	Calibres dérivés	Ø trou	Bloc dessus	Bloc dessous	Creusure plat. cad.		Clavette	Vis	Chaton empierré	Quartz <i>Quartz</i>		Ressort de c. pivot	
						dessus	dessous				dessus	dessous	dessus	dessous
• 2620	11½	2622 2630 2632 2638 2639	10	163.22.312	163.20	—	—	—	—	111.10	122.11	122.11	170.03	173.03
• 2720	11½	2722 2724 2728	09	164.22.312	173.20	—	—	—	—	111.09	122.11	122.11	170.03	173.03
• 2730	11½	2732 2734 2738	09	164.22.312	173.20	—	—	—	—	111.09	122.11	122.11	170.03	173.03
2412	6%		08	103.22.252	113.20	—	—	—	—	111.08	122.11	122.11	170.03	173.03
2442	6		08	103.22.252	113.20	—	—	—	—	111.08	122.11	122.11	170.03	173.03
2512	7%		09	103.22.278	113.20	10	20	—	—	111.09	122.11	122.11	170.03	173.03
2570	6%		08	104.22.232	113.20	—	—	—	—	111.08	122.11	122.11	173.03	173.03
2580			08	104.22.232	113.20	—	—	—	—	111.08	122.11	122.11	173.03	173.03
2640	7%	2641 2648 2660 2661 2668 2644 2645 2664 2665	08	104.22.232	113.20	—	—	—	—	111.09	122.11	122.11	173.03	173.03
2650	7%	2651 2658 2670 2671 2678 2688	08	104.22.232	113.20	—	—	—	—	111.09	122.11	122.11	173.03	173.03
2750	11½	2752 2758 2762 2763 2768 2769	10	163.22.312	163.20	—	—	—	—	111.10	122.11	122.11	170.03	173.03
2751	11½	2754 2760 2764 2766	09	163.22.312	163.20	—	—	—	—	111.09	122.11	122.11	170.03	173.03
2770	11½	2772 2773 2776 2778 2779 2782 2783 2788 2789	10	163.22.312	163.20	—	—	—	—	111.10	122.11	122.11	170.03	173.03
2771	11½	2774 2780 2784 2790	09	163.22.312	163.20	—	—	—	—	111.09	122.11	122.11	170.03	173.03
2800	11½ 13°	2802 2808 2803° 2809°	10	164.22.312	173.20	—	—	—	—	111.10	122.11	122.11	170.03	173.03
2801	11½ 13°	2804 2810 2805° 2811°	09	164.22.312	173.20	—	—	—	—	111.09	122.11	122.11	170.03	173.03
2819	11½ 13°	2806 2812 2807° 2813°	09	164.22.312	173.20	—	—	—	—	111.09	122.11	122.11	170.03	173.03
2820	11½ 13°	2822 2828 2823° 2829°	10	164.22.312	173.20	—	—	—	—	111.10	122.11	122.11	170.03	173.03
2821	11½ 13°	2824 2830 2825° 2831°	09	164.22.312	173.20	—	—	—	—	111.09	122.11	122.11	170.03	173.03
2839	11½ 13°	2826 2832 2827° 2833°	09	164.22.312	173.20	—	—	—	—	111.09	122.11	122.11	170.03	173.03

\* ETA 2801-1 09/164.22.312

2836-2 — upper bloc 09/164.22.312  
Lower bloc 09/173.20

Jewel hole box 8, endstone box 6, Springs upper box 80  
lower box 2

2893-2 = 2890-2



ETA 2688

08 | 104.22.232 | 113.20

122.11 | 111.08 | 111.09 | 173.03 | 173.03 = 02

Calibres de base	Grandeur	Calibres dérivés	Ø trou	Bloc dessus	Bloc dessous	Creusure plat. cad.	Clavette	Vis	Chaton empièré	Pierre de dessus	c. pivot dessous	Ressort de c. pivot dessus	Ressort de c. pivot dessous
<b>ETA</b>	<b>ETA SA</b>	<b>CH-2540 Grenchen</b>											
* 2510	7%	* 2512	09	100.21.282	110.20	10 20	180.15	160.11	111.09	122.11	122.11	170.03	170.03
2520	11½ 13*	2522 2523* 2532 2533* 2538 2539*	10	103.21.312	100.20	- -	180.15	160.11	111.10	122.11	122.11	170.03	170.03
2540	7%	2541	09	104.21.232	113.20	- -	180.15	-	111.09	122.11	122.11	173.03	173.03
2550	7%	2551	09	104.21.232	113.20	- -	180.15	-	111.09	122.11	122.11	173.03	173.03
2580	6%		08	104.22.232	113.20	- -	-	-	111.08	122.11	122.11	173.03	173.03
2600	11½	2602 2608 2609	10	163.22.312	163.20	- -	-	-	111.10	122.11	122.11	170.03	173.03
2620	11½	2622 2630 2632 2638 2639	10	163.22.312	163.20	- -	-	-	111.10	122.11	122.11	170.03	173.03
2720	11½	2722 2724 2728	09	164.22.312	173.20	- -	-	-	111.09	122.11	122.11	170.03	173.03
2730	11½	2732 2734 2738	09	164.22.312	173.20	- -	-	-	111.09	122.11	122.11	170.03	173.03
2800	11½ 13*	2802 2808 2803* 2809*	10	164.22.312	173.20	- -	-	-	111.10	122.11	122.11	170.03	173.03
2839	11½	2826 2832 2837	09	164.22.312	173.20	- -	-	-	111.09	122.11	122.11	170.03	173.03
* 2512	7%	* 2512-1	09	103.22.278	113.20	10 20	-	-	111.09	122.11	122.11	170.03	173.03
2640	7%	2641 2648 2660 2661 2868	08	104.22.232	113.20	- -	-	-	111.08	122.11	122.11	173.03	173.03
2650	7%	2651 2658 2670 2671 2678	08	104.22.232	113.20	- -	-	-	111.08	122.11	122.11	173.03	173.03
2750	11½	2752 2758 2762 2768 2769 2769-1	10	163.22.312	163.20	- -	-	-	111.10	122.11	122.11	170.03	173.03
2751	11½	2754 2760 2764 2766	09	163.22.312	163.20	- -	-	-	111.09	122.11	122.11	170.03	173.03
2771	11½	2774 2780 2784 2790 2790-1 2791	09	163.22.312	163.20	- -	-	-	111.09	122.11	122.11	170.03	173.03
2776	11½	2770 2772 2773 2778 2779 2781 2782 2783 2788 2789 2789-1	10	163.22.312	163.20	- -	-	-	111.10	122.11	122.11	170.03	173.03
2801	11½ 13*	2804 2810 2816 2814*	09	164.22.312	173.20	- -	-	-	111.09	122.11	122.11	170.03	173.03
2819	11½ 13*	2806 2812 2817 2818*	09	164.22.312	173.20	- -	-	-	111.09	122.11	122.11	170.03	173.03
2820	11½ 13*	2822 2828 2823* 2829*	10	164.22.312	173.20	- -	-	-	111.10	122.11	122.11	170.03	173.03
2821	11½ 13*	2824 2830 2836 2834* 2824-1 2834-1*	09	164.22.312	173.20	- -	-	-	111.09	122.11	122.11	170.03	173.03
2850	11½	2852 2858	09	163.22.312	926.20	- -	-	-	111.09 911.09	122.11	922.11	170.03	975.03
2851	11½	2853 2859	09	163.22.312	926.20	- -	-	-	111.09 911.09	122.11	922.11	170.03	975.03
2870	11½	2872 2878	09	163.22.312	926.20	- -	-	-	111.09 911.09	122.11	922.11	170.03	975.03
2871	11½	2873 2879	09	163.22.312	926.20	- -	-	-	111.09 911.09	122.11	922.11	170.03	975.03
2890	12½	2892	09	164.22.262	173.20	- -	-	-	111.09	122.11	122.11	170.03	173.03
2892-2 - check front page main CAT.													
* 2846	8¾ 10½		09	164.22.312	173.20				111.09	122.11	122.11	170.03	170.03
* 277.001	11½		08	164.22.262	956.20				111.09 911.09	122.11	922.11	170.03	975.03
2892.2	12½		09	164.22.262	956.20				111.09 911.09	122.11	922.11	170.03	975.03

2681

ETA 2890, 2892, 2890-2, 2890-A9, 2892-A2  
 2892-2, 2893-1, 2893-2, 2894-2, 2895-1,  
 2895-2, 2896, 2897

All above calibres are the same. For