

# Landeron

Fabrique d'Horlogerie de  
Fontainemelon SA  
Succursale du Landeron  
CH-2525 Le Landeron

| Calibres de base | Grandeur | Calibres dérivés |     |     | ∅<br>trou | Bloc<br>dessus | Bloc<br>dessous | Creusure<br>plat. cad. | Clavette | Vis    | Chaton<br>empierré | Pierre de<br>dessus | c. pivot<br>dessous | Ressort de c. pivot |         |        |
|------------------|----------|------------------|-----|-----|-----------|----------------|-----------------|------------------------|----------|--------|--------------------|---------------------|---------------------|---------------------|---------|--------|
|                  |          |                  |     |     |           |                |                 |                        |          |        |                    |                     |                     | dessus              | dessous |        |
| ° 48             | 13%      | 51               | 148 | 149 | 11        | 100.11.360     | 100.20          | —                      | —        | 180.19 | 150.11             | 111.11              | 121.11              | 122.11              | 170.03  | 170.03 |
|                  |          | 151              | 152 | 187 |           |                |                 |                        |          |        |                    |                     |                     |                     |         |        |
|                  |          | 189              | 248 | 349 |           |                |                 |                        |          |        |                    |                     |                     |                     |         |        |
| ° 523            | 13½      | 523 N            |     |     | 11        | 100.11.360     | 103.20          | —                      | —        | 180.19 | —                  | 111.11              | 121.11              | 122.11              | 170.03  | 173.03 |
| ° 2124           | 19       |                  |     |     | 12        | 500.13.440     | 500.20          | —                      | —        | —      | 560.41             | 511.12              | 521.11              | 522.11              | 570.03  | 570.03 |
| ° 4750           | 11½      | 4751             |     |     | 10        | 715.20.000     | 715.20          | —                      | —        | —      | —                  | 711.10              | 722.11              | 722.11              | 770.03  | 770.03 |

# Lavina

Manufacture d'horlogerie  
Favre-Leuba SA  
CH-1200 Genève

| Calibres de base | Grandeur | Calibres dérivés |  |  | ∅<br>trou | Bloc<br>dessus | Bloc<br>dessous | Creusure<br>plat. cad. | Clavette | Vis    | Chaton<br>empierré | Pierre de<br>dessus | c. pivot<br>dessous | Ressort de c. pivot |         |        |
|------------------|----------|------------------|--|--|-----------|----------------|-----------------|------------------------|----------|--------|--------------------|---------------------|---------------------|---------------------|---------|--------|
|                  |          |                  |  |  |           |                |                 |                        |          |        |                    |                     |                     | dessus              | dessous |        |
| ° 103            | 19 P     |                  |  |  | 12        | 500.13.430     | 500.20          | —                      | —        | —      | 560.41             | 511.12              | 521.11              | 522.11              | 570.03  | 570.03 |
| ° 115            | 8%       |                  |  |  | 08        | 100.11.265     | 110.20          | 10                     | —        | 180.19 | 150.11             | 111.08              | 121.11              | 122.11              | 170.03  | 170.03 |
| ° 120            | 10½      |                  |  |  | 10        | 100.11.300     | 100.20          | —                      | —        | 180.19 | 150.11             | 111.10              | 121.11              | 122.11              | 170.03  | 170.03 |
| ° 125            | 8¼×12    |                  |  |  | 11        | 100.11.320     | 100.20          | 10                     | —        | 180.19 | 150.11             | 111.11              | 121.11              | 122.11              | 170.03  | 170.03 |
| ° 102            | 16 EP    |                  |  |  | 12        | 500.11.365     | 500.20          | 15                     | —        | 580.25 | 560.41             | 511.12              | 521.11              | 522.11              | 570.03  | 570.03 |
| ° 105            | 13       |                  |  |  | 11        | 100.11.360     | 103.20          | —                      | —        | 180.19 | —                  | 111.11              | 121.11              | 122.11              | 170.03  | 173.03 |
| ° 140            | 5¼       |                  |  |  | 08        | 100.11.270     | 112.20          | 10                     | —        | 180.19 | 150.21             | 111.08              | 121.11              | 122.11              | 170.03  | 172.03 |
| ° 160            | 8%       |                  |  |  | 09        | 100.11.270     | 100.20          | 10                     | 9        | 180.19 | 150.11             | 111.09              | 121.11              | 122.11              | 170.03  | 170.03 |
| ° 170            | 5½       |                  |  |  | 08        | 100.11.260     | 112.20          | 10                     | 17       | 180.19 | 150.21             | 111.08              | 121.11              | 122.11              | 170.03  | 172.03 |
| ° 190            | 6%       |                  |  |  | 08        | 100.11.245     | 110.20          | 10                     | 5        | 180.19 | 150.11             | 111.08              | 121.11              | 122.11              | 173.03  | 170.03 |
| 150              | 10½ 11½* | 150 A*           |  |  | 09        | 100 11.300     | 100.20          | —                      | —        | 180.19 | 150.11             | 111.09              | 121.11              | 122.11              | 170.03  | 170.03 |