

Pierce

Montres Pierce SA
CH-2500 Bienne

Calibres de base	Grandeur	Calibres dérivés	∅ trou	Bloc dessus	Bloc dessous	Creusure plat. cad.	Clavette	Vis	Chaton empierré	Pierre de dessus	c. pivot dessous	Ressort de c. pivot dessus	Ressort de c. pivot dessous	
° 59	5¼		09	100.11.275	102.20	10	—	180.19	160.21	111.09	121.11	122.11	170.03	172.03
° 103 A	10½	103 SC 103 C	10	100.11.320	100.20	—	—	180.19	160.11	111.10	121.11	122.11	170.03	170.03
° 105	10½ 11½	105 SC 105 C	10	100.11.310	100.20	—	—	180.19	160.11	111.10	121.11	122.11	170.03	170.03
° 132	13	132 SC	10	100.11.310	100.20	10	—	180.19	160.11	111.10	121.11	122.11	170.03	170.03
° 134	13		10	100.11.310	100.20	—	—	180.19	160.11	111.10	121.11	122.11	170.03	170.03
° 135	13		10	100.11.310	100.20	—	—	180.19	160.11	111.10	121.11	122.11	170.03	170.03
° 516	5×7		09	100.11.275	102.20	10	—	180.19	160.21	111.09	121.11	122.11	170.03	172.03
° 861	8¼	861 SC 861 Aut.	09	100.11.265	100.20	11	—	180.19	160.11	111.09	121.11	122.11	170.03	170.03
° 1698	11½	1699	10	100.21.310	100.20	10	—	180.15	160.11	111.10	122.11	122.11	170.03	170.03
° 4200	11½	423 426	10	261.21.310	264.20	10	3	180.15	—	211.10	222.11	222.11	270.03	270.03
° 6344	13	6454	11	100.21.360	100.20	10	—	180.15	150.11	111.11	122.11	122.11	170.03	170.03

