

Calibres de base	Grandeur	Calibres dérivés	∅ trou	Bloc dessus	Bloc dessous	Creusure plat. cad.	Clavette	Vis	Chaton empierré	Pierre de dessus	c. pivot dessous	Ressort de dessus	c. pivot dessous
REVUE	Manufactures d'horlogerie Suisses Réunies SA CH-2300 La Chaux-de-Fonds												
°30	19	12	12	500.13.430	500.20	—	—	560.41	511.12	521.11	522.11	570.03	570.03
76	10½ 11½*	77*	09	100.11.310	100.20	10	15	180.19	150.11	111.09	121.11	170.03	170.03
77.1	11½		09	100.12.275	100.20	10	15	—	150.11	111.09	121.11	170.03	170.03
81	13		10	100.11.310	100.20	10	—	180.19	150.11	111.10	121.11	170.03	170.03
85	5½		08	100.11.260	103.20	10	—	180.19	—	111.08	121.11	170.03	173.03
L3	9¼ 11½*	P3*	10	944.12.293	945.20	—	—	—	911.10 991.10	921.11	222.11	974.03	876.03
N7	10½	N73 N76	10	973.22.263	906.20	—	—	—	911.10	922.11	922.11	974.03	975.03
P1	11½	P13 P16 P17 P18	10	973.22.263	906.20	—	—	—	911.10	922.11	922.11	974.03	975.03
P2	11½	P23 P26 P27	10	973.22.263	906.20	—	—	—	911.10	922.11	922.11	974.03	975.03

Revue

Manufactures d'Horlogerie Suisses
Réunies SA
CH-2300 La Chaux-de-Fonds

Calibres de base	Grandeur	Calibres dérivés	∅ trou	Bloc dessus	Bloc dessous	Creusure plat. cad.	Clavette	Vis	Chaton empierré	Pierre de dessus	c. pivot dessous	Ressort de dessus	c. pivot dessous
° 42	8%		09	100.11.265	100.20	10	—	180.19	150.11	111.09	121.11	170.03	170.03
° 49	7%		08	100.11.240	103.20	10	17	180.19	—	111.08	121.11	173.03	173.03
° 51	18½		12	500.11.400	500.20	15	10	580.25	560.41	511.12	521.11	570.03	570.03
° 56	10½ 11½*	57*	10	100.11.310	100.20	10	—	180.19	150.11	111.10	121.11	170.03	170.03
° 59	12		10	100.11.310	100.20	10	—	180.19	150.11	111.10	121.11	170.03	170.03
° 78	8% 9%* 12½**	79* 80**	08	100.11.265	100.20	10	17	180.19	150.11	111.08	121.11	170.03	170.03
° 82	8%		09	100.11.265	100.20	10	—	180.19	150.11	111.09	121.11	170.03	170.03
° 87	11½		09	160.12.265	164.20	10	—	—	111.09	121.11	122.11	170.03	173.03
° 88	5½		08	100.11.250	113.20	10	9	180.19	—	111.08	121.11	170.03	173.03
° 205	5½		08	100.11.255	112.20	10	—	180.19	150.21	111.08	121.11	170.03	172.03
° 211	11½		10	100.11.317	100.20	—	—	180.19	150.11	111.10	121.11	170.03	170.03
° 212	7%		09	100.21.255	231.20	10	15	180.15	150.21	111.09 211.09	122.11	222.11	170.03 270.03
° 213	7%		09	100.11.255	110.20	—	—	180.19	160.11	111.09	121.11	170.03	170.03
° 214	11½		09	100.21.275	103.20	10	—	180.15	—	111.09	122.11	170.03	173.02
° 215	10½		10	100.21.317	100.20	—	—	180.15	160.11	111.10	122.11	170.03	170.03
30	19		12	500.13.430	500.20	—	—	560.41	511.12	521.11	522.11	570.03	570.03
76	10½ 11½*	77*	09	100.11.310	100.20	10	15	180.19	150.11	111.09	121.11	170.03	170.03
77.1	11½		09	100.12.275	100.20	10	15	—	150.11	111.09	121.11	170.03	170.03
81	13		10	100.11.310	100.20	10	—	180.19	150.11	111.10	121.11	170.03	170.03
85	5½		08	100.11.260	103.20	10	—	180.19	—	111.08	121.11	170.03	173.03

Q 101-22245

670