

Roamer

Roamer Watch Co. SA
CH-4500 Soleure

Calibres de base	Grandeur	Calibres dérivés	∅ trou	Bloc dessus	Bloc dessous	Creusure plat. cad.	Clavette	Vis	Chaton empierré	Pierre de dessus	c. pivot dessous	Ressort de dessus	c. pivot dessous	
° 297	19,4 mm		09	100.11.265	100.20	10	—	180.19	150.11	111.09	121.11	122.11	170.03	170.03
° 302	19,9×26,4 mm		11	100.11.310	100.20	—	—	180.19	150.11	111.11	121.11	122.11	170.03	170.03
° 340	15,3×17,8 mm	381	09	100.11.260	100.20	10	—	180.19	160.11	111.09	121.11	122.11	170.03	170.03
° 348	17,5×25 mm		10	100.11.265	100.20	10	—	180.19	150.11	111.10	121.11	122.11	170.03	170.03
° 349	12,8×19,2 mm		09	100.11.260	100.20	10	—	180.15	160.11	111.09	121.11	122.11	170.03	170.03
° 366	13×15,2 mm		08	100.11.260	112.20	10	—	180.19	150.11	111.08	121.11	122.11	170.03	172.03
° 367	19,4 mm	422	09	100.11.260	100.20	10	7	180.19	160.11	111.09	121.11	122.11	170.03	170.03
° 373	19,4 mm		09	100.11.260	100.26	10	—	180.19	160.11	111.09	121.11	122.11	170.03	170.03
° 389	13×15,2 mm		09	201.11.210	211.20	—	—	280.21	150.21	211.09	221.11	222.11	270.03	270.03
° 396	15,3×17,8 mm		08	100.11.260	100.20	10	—	180.19	160.11	111.08	121.11	122.11	170.03	170.03
° 400	23,4 mm 25,6 mm*	401* 416*	10	100.11.290	100.20	10	—	180.15	160.11	111.10	121.11	122.11	170.03	170.03
° 400	23,4 mm		10	100.11.290	103.20	10	—	180.15	—	111.10	121.11	122.11	170.03	170.03
° 402	30 mm	428	11	100.11.290	100.20	10	—	180.19	160.11	111.11	121.11	122.11	170.03	170.03
° 409	17,5×25 mm		10	100.11.260	100.20	10	—	180.19	160.11	111.10	121.11	122.11	170.03	170.03
° 410	26 mm	411	09	100.11.260	100.20	10	7	180.19	160.11	111.09	121.11	122.11	170.03	170.03
° 413	23,3 mm 25,6 mm*	414* 415 430*	09	100.11.290	100.20	—	—	180.15	160.11	111.09	121.11	122.11	170.03	170.03
° 413	23,3 mm 25,6 mm	414* 415 430*	09	100.11.290	103.20	—	—	180.15	—	111.09	121.11	122.11	170.03	173.03
° 417	27 mm	427	10	100.11.290	100.20	—	—	180.19	160.11	111.10	121.11	122.11	170.03	170.03
° 420	26 mm		09	100.11.290	100.20	—	—	180.19	160.11	111.09	121.11	122.11	170.03	170.03
° 423	19,4 mm		09	100.11.260	100.20	10	10	180.15	160.11	111.09	121.11	122.11	170.03	170.03
° 424	28 mm	425	10	100.11.290	100.20	10	—	180.15	160.11	111.10	121.11	122.11	170.03	170.03
° 424-03	28 mm	425-03 Incastar	10	100.11.290	103.20	10	—	180.15	—	111.10	121.11	122.11	170.03	173.03
° 429	17,2 mm		09	201.11.210	211.20	10	7	280.21	150.21	211.09	221.11	222.11	270.03	270.03
° 431	16 mm		09	201.11.210	211.20	10	7	280.21	150.21	211.09	221.11	222.11	270.03	270.03
° 436	26 mm	437	09	100.11.290	103.20	—	—	180.15	—	111.09	121.11	122.11	170.03	173.03
° 439	17,2 mm	465	08	100.11.255	110.20	—	—	180.19	160.11	111.08	121.11	122.11	170.03	170.03
° 440	15,3×17,8 mm		09	100.11.260	103.20	10	—	180.15	—	111.09	121.11	122.11	170.03	173.03
° 441	26 mm	452	10	100.11.310	100.20	10	—	180.19	160.11	111.10	121.11	122.11	170.03	170.03
° 450	19,4 mm	451	09	100.21.260	101.20	10	22	180.15	160.11	111.09	122.11	122.11	170.03	171.03
° 467	15,3 mm		09	205.21.210	213.20	—	—	280.17	—	211.09	222.11	222.11	270.03	270.03
° 472	17,2 mm	473	09	104.21.232	113.20	—	—	180.15	—	111.09	122.11	122.11	173.03	173.03
° 474	25,6 mm	477	10	103.21.312	100.20	—	—	180.15	160.11	111.10	122.11	122.11	170.03	170.03
° 475	19,4 mm	476	09	264.21.230	213.20	10	10	180.15	—	211.09	222.11	222.11	270.03	270.03
° 478	25,6 mm	479	10	163.22.312	163.20	—	—	—	—	111.10	122.11	122.11	170.03	173.03
° 800	15,3×17,8 mm	803	09	103.22.232	103.20	10	—	—	—	111.09	122.11	122.11	173.03	173.03



Roamer

Roamer Watch Co. SA
CH-4500 Soleure

Calibres de base	Grandeur	Calibres dérivés	∅ trou	Bloc dessus	Bloc dessous	Creusure plat. cad.	Clavette	Vis	Chaton empierré	Pierre de dessus	c. pivot dessous	Ressort de dessus	c. pivot dessous	
293	36 mm		11	193.12.415	100.20	10	—	160.11	111.11	121.11	122.11	170.03	170.03	
448	25,6 mm 23,3 mm*	449 481°	09	261.21.302	264.20	10	12	180.15	—	211.09	222.11	222.11	270.03	270.03
466	13,5×15,2 mm 15,3 mm*	468	08	205.21.210	213.20	—	—	280.17	—	211.08	222.11	222.11	270.03	270.03
469	17,2 mm		09	205.21.210	213.20	10	7	280.17	—	211.08	222.11	222.11	270.03	270.03
470	26 mm	471	09	100.11.290	103.20	—	—	180.15	—	111.09	121.11	122.11	170.03	173.03
480	13,5 mm		08	103.21.252	113.20	—	—	180.15	—	111.08	122.11	122.11	170.03	173.03
482	25,6 mm	483	10	163.22.312	163.20	—	—	—	—	111.10	122.11	122.11	170.03	173.03
484	17,2 mm		09	104.22.232	113.20	—	—	—	—	111.09	122.11	122.11	173.03	173.03
485	17,2 mm		08	104.22.232	113.20	—	—	—	—	111.08	122.11	122.11	173.03	173.03
486	13×15 mm		08	914.22.230	937.20	—	—	—	—	911.08	922.11	922.11	975.03	975.03
487	23,3 mm		09	944.22.290	946.20	10	13	—	—	911.09	922.11	922.11	974.03	975.03
520	25,6 mm	510 513 521 522 523	09	953.22.263	926.20	—	—	—	—	911.09	922.11	922.11	974.03	975.03
801	25,6 mm	802	09	103.22.292	103.20	—	—	—	—	111.09	122.11	122.11	170.03	173.03
915	12½		10	706.21.000	706.21	—	—	—	—	711.10	722.11	722.11	775.03	775.03
916	12½		10	726.21.000	726.21	—	—	—	—	711.10	722.11	722.11	775.03	775.03

ROAMER Roamer Watch Co. SA CH-4500 Soleure

°293	36 mm		11	193.12.415	100.20	10	—	160.11	111.11	121.11	122.11	170.03	170.03	
°349	12,8×19,2 mm		09	100.11.260	100.20	10	—	180.15	160.11	111.09	121.11	122.11	170.03	170.03
°367	19,4 mm	422	09	100.11.260	100.20	10	7	180.19	160.11	111.09	121.11	122.11	170.03	170.03
°373	19,4 mm		09	100.11.260	100.20	10	—	180.19	160.11	111.09	121.11	122.11	170.03	170.03
°389	13×15,2 mm		09	201.11.210	211.20	—	—	280.21	150.21	211.09	221.11	222.11	270.03	270.03
°396	15,3×17,8 mm		08	100.11.260	100.20	10	—	180.19	160.11	111.08	121.11	122.11	170.03	170.03
°400	23,4 mm		10	100.11.290	103.20	10	—	180.15	—	111.10	121.11	122.11	170.03	173.03
°402	30 mm	428	11	100.11.290	100.20	10	—	180.19	160.11	111.11	121.11	122.11	170.03	170.03
°409	17,5×25 mm		10	100.11.260	100.20	10	—	180.19	160.11	111.10	121.11	122.11	170.03	170.03
°413	23,3 mm 25,6 mm*	414* 415 430*	09	100.11.290	103.20	—	—	180.15	—	111.09	121.11	122.11	170.03	173.03
°420	26 mm		09	100.11.290	100.20	—	—	180.19	160.11	111.09	121.11	122.11	170.03	170.03
°423	19,4 mm		09	100.11.260	100.20	10	10	180.15	160.11	111.09	121.11	122.11	170.03	170.03
°424	28 mm	425	10	100.11.290	100.20	10	—	180.15	160.11	111.10	121.11	122.11	170.03	170.03
°429	17,2 mm		09	201.11.210	211.20	10	7	280.21	150.21	211.09	221.11	222.11	270.03	270.03
°431	16 mm		09	201.11.210	211.20	10	7	280.21	150.21	211.09	221.11	222.11	270.03	270.03
°436	26 mm	437	09	100.11.290	103.20	—	—	180.15	—	111.09	121.11	122.11	170.03	173.03
°439	17,2 mm	465	08	100.11.255	110.20	—	—	180.19	160.11	111.08	121.11	122.11	170.03	170.03
°440	15,3×17,8 mm		09	100.11.260	103.20	10	—	180.15	—	111.09	121.11	122.11	170.03	173.03
°441	26 mm	452	10	100.11.310	100.20	10	—	180.19	160.11	111.10	121.11	122.11	170.03	170.03
°448	25,6 mm 23,3 mm*	449 481*	09	261.21.302	264.20	10	12	180.15	—	211.09	222.11	222.11	270.03	270.03
°450	19,4 mm	451	09	100.21.260	101.20	10	22	180.15	160.11	111.09	122.11	122.11	170.03	171.03
°466	13,5×15,2 mm 15,3 mm*	468	08	205.21.210	213.20	—	—	280.17	—	211.08	222.11	222.11	270.03	270.03
°467	15,3 mm		09	205.21.210	213.20	—	—	280.17	—	211.09	222.11	222.11	270.03	270.03
°469	17,2 mm		09	205.21.210	213.20	10	7	280.17	—	211.09	222.11	222.11	270.03	270.03
°470	26 mm	471	09	100.11.290	103.20	—	—	180.15	—	111.09	121.11	122.11	170.03	173.03
°472	17,2 mm	473	09	104.21.232	113.20	—	—	180.15	—	111.09	122.11	122.11	173.03	173.03