

Calibre No.

**5626A**

Jewels

**25j**

Style Name

⇨ Basic Calibre **5606A** <sup>23J</sup>/<sub>25J</sub> Catalog No. 56-06-1

Cal. 5626A

### Characteristics

Casing diameter:	25.60 <sup>±</sup> mm
Maximum height:	4.50 mm
Vibrations per hour:	28,800
Automatic and auxiliary hand winding with sweep second	
Calendar (day & date)	
Instant setting device for day & date calendar	
Bilingual change-over system for day of week	
Second-setting device	
Outside micro-adjusting device	
"Diashock"	Shock Resistant Device
"Diafix"	Oil Lubrication Device



112561



171561



401565



251561



301561



310561



341561



344561



793561



285561



391561



509563



☆870563

☆⇨ Please see remarks on the next page.

As for all other parts not shown here, please refer to the basic calibre

(Cal. No. **5606A** <sup>23J</sup>/<sub>25J</sub> Catalog No. 56-06-1 Green page).

Calibre No.

**5626A**

Jewels

**25j**

Style Name

⇨ Basic Calibre **5606A** <sup>23J</sup>/<sub>25J</sub> Catalog No. 56-06-1

PART NO.	LIST OF MATERIALS	PART NO.	LIST OF MATERIALS
<b>112561</b>	<b>Barrel &amp; train-wheel bridge</b>	868560	Day finger
161560	Pallet cock	☆ <b>870563</b>	<b>Day star with dial disk</b>
<b>171561</b>	<b>Balance cock</b>	873560	Day jumper
189560	Transmission wheel bridge	☆ 884560	Holding ring for dial
205560	Complete barrel with arbor	963610	Snap for day star with dial disk
213560	Barrel arbor	981560	Day-date corrector wheel rocker
220560	Large driving wheel & pinions	986560	Day-date corrector wheel rocking lever
225560	Cannon pinion	987560	Day-date corrector wheel rocking lever spring
231560	Third wheel & pinion	989560	Intermediate wheel for day correction
241560	Sweep second wheel & pinion	022150	Stud screw
<b>251561</b>	<b>Escape wheel &amp; pinion</b>	022252	Transmission wheel bridge screw
261560	Minute wheel	022257	Screw for day-date corrector wheel rocking lever spring
271611	Hour wheel	022373	Pallet cock screw
282560	Clutch wheel	022454	Screw for reverser idler bolt
283560	Winding pinion	022458	Screw for oscillating weight
<b>285561</b>	<b>Ratchet wheel</b>	022467	Ratchet wheel screw
<b>301561</b>	<b>Jewelled pallet fork &amp; staff</b>	022482	Screw for intermediate wheel of day correction
<b>310561</b>	<b>Balance complete with stud</b>	022484	Bridge screw
315560	Balance staff	022486	Minute wheel bridge screw
331560	Roller with jewel	022662	Setting lever spring screw
<b>341561</b>	<b>Regulator</b>	022667	Second-setting lever screw
<b>344561</b>	<b>Regulator adjusting device</b>	022673	Screw for day & date driving wheel
345612	Stud holder	022674	Screw for day-date corrector wheel rocking lever
354560	Winding stem	022753	Date dial guard screw
361560	Second-setting lever spring	022753	Day jumper screw
367560	Minute wheel spring	022761	Dial screw
381560	Click	011123	Upper hole jewel for barrel
☆ 383560		011142	Lower hole jewel for barrel
☆ 383561	Setting lever	011147	Upper hole jewel for large driving wheel & pinions
☆ 383562		011147	Lower hole jewel for large driving wheel & pinions
384560	Yoke (Clutch lever)	011323	Lower hole jewel for 3rd wheel
385560	Yoke spring (Clutch lever spring)	011423	Lower hole jewel for escape wheel
387560	Minute wheel bridge	011503	Upper hole jewel for pallet
388560	Setting lever spring	011503	Lower hole jewel for pallet
390560	Setting lever axle	011147	Lower hole jewel for 1st reverser idler
<b>391561</b>	<b>Second-setting lever</b>	011151	Upper hole jewel for differential wheel
<b>401565</b>	<b>Mainspring with slipping attachment</b>	011133	Lower hole jewel for differential wheel
<b>793561</b>	<b>Micro-adjusting axle</b>	011159	Upper hole jewel for transmission wheel
014363	Diashock upper frame	011159	Lower hole jewel for transmission wheel
014384	Diashock lower frame	023179	Tube for minute wheel bridge screw
014365	Diashock hole jewel with frame	023180	Tube for bridge screw (Cylinder type)
011210	Diashock cap jewel	023184	Tube for bridge screw (Recessed type)
014317	Diashock spring		
015421	Diafix upper hole jewel with frame for 3rd wheel		
015411	Diafix upper hole jewel with frame for escape wheel		
011206	Diafix cap jewel		
015113	Diafix spring		
<b>509563</b>	<b>Oscillating weight with ball-bearing</b>		
505560	Transmission wheel		
531560	Differential wheel		
848560	First reverser idler		
851560	Second reverser idler		
854560	Reverser idler bolt		
☆ 801560	Date dial		
802560	Date driving wheel		
803560	Setting wheel lever complete		
808560	Date dial guard		
810560	Date jumper		
812560	Setting wheel lever spring		
817610	Intermediate date wheel		

☆ ⇨ Please see remarks on the next page.

Items in light letters are not shown in photos; those parts are interchangeable with the basic calibre

(Cal. No. **5606A** <sup>23J</sup>/<sub>25J</sub> Catalog No. 56-06-1 Green page).

Calibre No.

**5626A**

Jewels

**25 j**

Style Name

⇨ Basic Calibre **5606A** <sup>23</sup>/<sub>25</sub> Catalog No. 56-06-1**Remarks :****Setting lever**

There are three types of setting levers, used according to the dial diameter. Select the suitable setting lever by referring to the shapes indicated in fig. 1.

When a setting lever unsuitable for the dial diameter is used, the winding stem cannot be pulled out or the movement cannot be assembled in the case. Pay attention to this point (refer to fig. 2).

When the dial is round, the number of the setting lever differs (listed below) according to the dial diameter.

(Dial diameter) 25.5 ~ 26.5  $\phi$ mm ..... ☆ 383561  
 ( " ) 27.5 ~ 28.5  $\phi$ mm ..... ☆ 383560  
 ( " ) 29.5 ~ 30.5  $\phi$ mm ..... ☆ 383562

If the number of the setting lever is unknown or when placing an order for a setting lever other than those mentioned above, specify ① Cal. No. and ② the dial No.

(fig. 1)



☆ 383560



☆ 383561



☆ 383562

(fig. 2)

When the setting lever is too small

✗



Setting lever is hidden under the dial and the winding stem cannot be pulled out.

When the setting lever is too large

✗



Blocked by the setting lever, the movement cannot be assembled in the case.

Correct

○



End of the setting lever is located between the dial and the case.

**Date dial**

☆ 801560 ..... Used when both the crown and the date frame are located at 3 o'clock.

If the date dial is required in any other type, specify ① Cal. No. ② the crown position ③ the date frame position and ④ the dial No.

**Day star with dial disk**

☆ 870563 ..... Used when both the crown and the day frame are located at 3 o'clock.

When ordering any other type of the day star with dial disks, clearly mention the number printed on the disk. If the number is unknown, specify ① Cal. No. ② the crown position ③ the day frame position ④ the dial No. and ⑤ the national language.

**Holding ring for dial** — Measure the total thickness and the outside diameter —

☆ 884560 ..... 0.53 mm total thickness and 27.0  $\phi$ mm outside diameter.

If the holding ring for dial is required in any other type, specify ① Cal. No. and ② the dial No.